

ETS-210TW/WS - PA Speaker Column



Slim Design, Weatherproof Version
PA column speakers,
in extruded aluminium cabinets.

- Weatherproof and hose-proof
- 100 V line technique
- 2-way version (with additional integrated tweeters for a clearly improved sound)
- Connection cable with 5-step power taps
- 2 x M6 threaded bushing
- Aluminium front grille
- Supplied with mounting brackets

Tekniset tiedot:

Active/passive	: passive
Transmission method	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 10/5/2.5/1.25/0.63Â W
Impedance	: -
Frequency range	: 170-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 2+1
Speaker size	: -
Sensitivity	: 86 dB/W/m
Max. rated SPL	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: aluminium
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: -
Protection class	: IP66
Admiss. ambient temp.	: -20 °C to +50 °C
Power supply	: -
Dimensions	: 80 x 280 x 70 mm
Width	: 80 mm
Height	: 280 mm
Depth	: 70 mm
Weight	: 1 kg



Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -