



ESP-250/WS - PA Wall Speaker



PA speaker system,
in a weatherproof white plastic cabinet with aluminium protective grille.

- 100 V line technique
- Hose-proof
- Switchable to 8 Ohm operation
- 5 power taps, 8 Ohm connection and 100 V power selector switch
- 2-way system
- Stainless steel mounting bracket

Tekniset tiedot:

| | |
|--------------------------------|--|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : 100 W |
| Power rating (RMS) | : 50/40/30/20/10 W (100 V) 50 W (8 Ohm) |
| Impedance | : 8 Ohm |
| Frequency range | : 80-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : 2-way |
| Full range speaker | : - |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : - |
| Speaker size | : - |
| Sensitivity | : 92 dB/W/m |
| Max. rated SPL | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : plastic |
| Colour | : white |
| Mounting device | : - |
| Protected against ball rebound | : - |
| Protection class | : IP65 |
| Admiss. ambient temp. | : -20 °C to +50 °C |
| Power supply | : - |
| Dimensions | : 157 x 260 x 170 mm |
| Width | : 157 mm |
| Height | : 260 mm |
| Depth | : 170 mm |
| Weight | : 2.4 kg |



| | |
|------------------------|------------------------------|
| Inputs | : spring-load. speaker term. |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |