

## FGA-202 - Line Isolator



Professional 2-channel line transformer,  
for reducing signal interference and hum loops.

- 2 inputs via balanced comb. jacks XLR/6.3 mm (600 Ohm)
- 2 galvanically isolated XLR outputs (600 Ohm) with ground lift switch
- Frequency range: 20-20,000 Hz
- Robust metal housing with very good shielding qualities, suitable for stage applications
- Dimensions: 125 x 55 x 75 mm
- Weight: 650 g

SOUNDCHECK 07/2007

on the FGA-102, FGA-202, LC-31, MC-31 and LSP-102:

"Every musician or sound engineer should have these little helpers in their toolbox. They impress by their unobtrusiveness. Both the robust metal housing and the functionality of these transformers allow to solve many problems on stage or in the studio at a reasonable price."

tools4music 06/2009

on the LSP-102, LC-31, FGA-102, FGA-202, DIB-102

"Recommendable and fit for on-the-road applications. An attractively priced little audio aid, perfect for the 'ever accompanying' tool case."

## Tekniset tiedot:

|                       |                                   |
|-----------------------|-----------------------------------|
| Description           | : transformer                     |
| Frequency range       | : 20-20,000 Hz                    |
| Control range         | : -                               |
| Control frequencies   | : -                               |
| Input signal          | : -                               |
| Input sensitivity     | : -                               |
| Input impedance       | : 600 Ohm                         |
| Output signal         | : -                               |
| Output impedance      | : 600 Ohm                         |
| Gain                  | : -                               |
| Phantom power         | : -                               |
| Compression           | : -                               |
| Gate ratio            | : -                               |
| Crossover frequency   | : -                               |
| High-pass filter      | : -                               |
| Low cut               | : -                               |
| Transmission ratio    | : -                               |
| S/N ratio             | : -                               |
| Channel separation    | : -                               |
| THD                   | : -                               |
| Admiss. ambient temp. | : 0-40 °C                         |
| Power supply          | : -                               |
| Dimensions            | : 125 x 55 x 75 mm                |
| Weight                | : 650 g                           |
| Inputs                | : 2 x comb. jack XLR/6.3 mm, bal. |
| Outputs               | : 2 x XLR                         |
| Other features        | : -                               |