

ILA-100XLR - Attenuator



Passive stereo level control (XLR version),
for a precise volume control of line signals,
for inserting between analogue signal sources and amplifiers or active speakers, e.g. between a PC sound
card and active speaker systems.

- 2 x balanced comb. input (XLR/6.3 mm jack), 1 x 3.5 mm stereo input
- 2 x balanced XLR output, 1 x 3.5 mm stereo output
- Large, easy-turning level control
- Mute button
- Frequency range: 20-20,000 Hz
- Passive, no power supply required
- High-quality metal console housing with brushed aluminium front panel
- Dimensions: 142 x 60 x 86 mm
- Weight: 300 g

Tekniset tiedot:

| | |
|------------------------|--|
| Impedance | : - |
| Line input | : - |
| Input control voltage | : - |
| Line output | : - |
| Output control voltage | : - |
| Channels | : 2 |
| Attenuation | : - |
| Attenuation direction | : - |
| Turning angle | : - |
| Frequency range | : 20-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Power rating | : - |
| Power supply | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : 142 x 60 x 86 mm |
| Weight | : 300 g |
| Connections | : 2 x comb. balanced input (XLR/6.3 mm jack), 1 x 3.5 mm stereo input, 2 x balanced XLR output, 1 x 3.5 mm stereo output |