


SPE-32/WS - Loudspeaker

8Ω



Hi-fi wall and ceiling speakers, 8 Ohm

- 2-way version with dome tweeter (movable with SPE-17/WS, SPE-22/WS and SPE-32/WS)
- Plastic housing with protective metal grille
- ABS plastic material, self-extinguishing according to UL 94V-0
- Excellent sound characteristics
- For a wall thickness/ceiling thickness from 8 to 35 mm

Tekniset tiedot:

| | |
|---|---------------------|
| Impedance (Z) | : 8 Ohm |
| Transmission method | : - |
| Frequency range | : 40-20,000 Hz |
| Resonant frequency (fs) | : 37 Hz |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | : - |
| Power rating (RMS) | : 50 W |
| Peak music power output (MAX) | : 100 W |
| Sensitivity | : 89 dB/W/m |
| Max. rated SPL | : - |
| Max. voltage | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Suspension compl. (Cms) | : - |
| Moving mass (Mms) | : - |
| Mech. Q factor (Qms) | : - |
| Electr. Q factor (Qes) | : - |
| Total Q factor (Qts) | : - |
| Equivalent volume (Vas) | : - |
| DC resistance (Re) | : - |
| Force factor (BxL) | : - |
| Voice coil induct. (Le) | : - |
| Voice coil diameter | : - |
| Voice coil former | : - |
| Linear excursion (X _{MAX}) | : - |
| Eff. cone area (Sd) | : - |
| Magnet weight | : - |
| Magnet diameter | : - |
| Mounting cutout | : 330 x 225 mm |
| Mounting depth | : 87 mm |
| Mounting hole diameter | : - |
| Hole spacing X-axis | : - |
| Hole spacing Y-axis | : - |
| Dimensions | : 358 x 256 x 97 mm |
| Outside diameter | : - |
| Width | : 358 mm |

| | |
|-----------------------|-----------|
| Height | : 256 mm |
| Depth | : - |
| Protective class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Weight | : 2.19 kg |
| Packing unit | : 1 |
| Type of speaker | : 200 |