

## DRUMSET-1 - Microphone Set



7-piece drum microphone set,  
consisting of a dynamic bass drum microphone, four dynamic snare drum/tom-tom microphones and two  
overhead condenser microphones.

- Optimised for sound pickup of drums
- Short-bodied microphones
- Including microphone holder with 16 mm ((tm)) tripod socket and 9 mm ((tm)) adapter screw for every microphone
- Additional clamps for the snare drum/tom-tom microphones
- Supplied in a practical plastic case

## Tekniset tiedot:

|                         |   |
|-------------------------|---|
| Description             | : drum microphones  |
| Version                 | : -   |
| Transmission method     | : cable   |
| Polar pattern           | : bi-directional (bass drum) supercardioid (snare drum/tom-tom) cardioid (overhead)                                     |
| System                  | : dynamic (bass drum) dynamic (snare drum/tom-tom) electret (overhead)  |
| Carrier frequency range | : -   |
| Transmitting power      | : -   |
| Power supply            | : -   |
| Operating time          | : -   |
| Audio frequency range   | : 50-10,000 Hz (bass drum) 50-15,000 Hz (snare drum/tom-tom) 50-15,000 Hz (overhead)                                    |
| Nominal impedance       | : 200 Ohm   |
| Sensitivity             | : 1.6 mV/Pa (bass drum) 2.5 mV/Pa (snare drum/tom-tom) 5.6 mV/Pa (overhead)   |
| S/N ratio               | : 66 dB   |
| Max. sound pressure     | : 158 dB (bass drum) 157 dB (snare drum/tom-tom) 161 dB (overhead)  |
| Power supply            | : DC 48 V, phantom power (overhead)   |
| Gooseneck length        | : -   |
| Housing material        | : -   |
| Admiss. ambient temp.   | : 0-40 °C   |
| Dimensions              | : ~ 50 mm x 113 mm (bass drum) ~ 40 mm x 93 mm (snare drum/tom-tom) ~ 22 mm x 90 mm (overhead) 430 x 135 x 320 mm (set) |
| Weight                  | : 1.5 kg  |
| Cable                   | : -   |
| Connection              | : XLR, bal.   |