

## TXS-2402SET - Wireless Microphone



With the TXS-2402SET, the entry into the world of digital wireless transmission will become a special sound experience. The signal transmission in the 2.4 GHz range is particularly stable and impresses by a high resistance to interference. The system manages without a compander which results in an incredibly dynamic efficiency and a voice transmission with a unique sound quality. Two systems can be used in parallel operation, thus 4 microphone transmission paths can be used simultaneously. Licence-free system. The particularly easy and convenient use of the units and appealing design make the TXS-2402SET a real digital experience for the user. Digital wireless 2-channel PLL microphone system, 2.4 GHz

- 2 microphone transmitters, 1 receiver, 1 plug-in PSU
- High resistance to interference due to digital transmission
- 2 systems can be used in parallel (corresponds to 4 microphone transmission paths)
- 16 frequencies (2,404-2,476 MHz) for each channel can be selected at the transmitter
- Wireless auto-configuration of the receiver
- Volume control for each channel
- 6.3 mm output for mixed signal
- Microphone cartridges of supercardioid characteristic

Licence-free in the EU.

tastenwelt 06/2012

“An entry-level wireless system with a perfectly functioning technology.”

+ Easy operation

+ Well-balanced hand-held transmitter

## Tekniset tiedot:

### General information

	: -
Description	: wireless microphone system
Carrier frequency range	: 2,404-2,476 MHz
Audio frequency range	: 80-12,000 Hz
Channels	: 2
THD	: < 0.1%
Dynamic range	: 87 dB
RF S/N ratio	: -
Operating time	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: -
Total weight	: -
Connections	: -

### Specifications transmitter

	: -
Transmitting power	: 10 mW
Operating range	: approx. 30 m (free field) approx. 20 m (indoors)

Power supply transmitter	: 2 x 1.5 V batt. AA size
Width transmitter	: 54 mm
Height transmitter	: 54 mm
Depth transmitter	: 225 mm
Weight transmitter	: 120 g
Connections transmitter	: -

### Specifications receiver

	: -
Audio signal receiver	: 100 mV/600 Ohm
Power supply receiver	: via encl. plug-in power supply
Width receiver	: 220 mm
Height receiver	: 45 mm
Depth receiver	: 150 mm
Weight receiver	: 550 g
Connections receiver	: 1 x 6.3 mm jack, unbal.