

TXS-900HT - Handheld Transmitter



Hand-held microphone with integrated multifrequency transmitter, with UHF PLL technology.

- Condenser microphone cartridge, cardioid polar pattern
- 2 frequency ranges (E band: 823-832 MHz and 863-865 MHz)
- SYNC function for synchronisation with receivers TXS-900 and TXS-920
- Mute function
- LCD for indicating channel and battery status
- Power supply via 2 x 1.5 V battery AA size (not supplied)

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

SOUNDCHECK 11/2014

"The transmission systems of the TXS series are perfectly equipped for the future and with the latest technology ensure an interference-free transmission on a big stage."

- + Easy configuration
- + Interference-free transmission
- + Impressive over greater distances

Tekniset tiedot:

| | |
|-------------------------|------------------------------------|
| Description | : hand-held microphone transmitter |
| Version | : - |
| Transmission method | : wireless |
| Polar pattern | : cardioid |
| System | : condenser |
| Carrier frequency range | : 823-832 MHz + 863-865 MHz |
| Transmitting power | : 10 mW |
| Power supply | : 2 x 1.5 batt. AA size |
| Operating time | : ? 15 h |
| Audio frequency range | : 80-18,000 Hz |
| Nominal impedance | : - |
| Sensitivity | : - |
| S/N ratio | : - |
| Max. sound pressure | : - |
| Power supply | : - |
| Gooseneck length | : - |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : ~ 53 mm x 260 mm |
| Weight | : 220 g |
| Cable | : - |
| Connection | : - |