

TXS-900HSE - Microphone Transmitter



Multifrequency pocket transmitter,
with UHF PLL technology.

- 2 frequency ranges
- SYNC function for synchronisation with receivers TXS-900 and TXS-920
- Mute function
- Sensitivity can be adjusted in 3 steps
- LCD for indicating channel and battery status
- Suitable for combination with headband/earband microphones and tie clip microphones with 3-pole mini XLR connector
- Belt clip
- Power supply via 2 x 1.5 V battery AA size (not supplied)

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

Tekniset tiedot:

General information

| | |
|-------------------------|-----------------------------|
| | : - |
| Description | : pocket transmitter |
| Carrier frequency range | : 823-832 MHz + 863-865 MHz |
| Audio frequency range | : 80-18,000 Hz |
| Channels | : 1 |
| THD | : - |
| Dynamic range | : - |
| RF S/N ratio | : - |
| Operating time | : ? 15 h |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : - |
| Total weight | : - |
| Connections | : - |

Specifications transmitter

| | |
|--------------------------|---------------------------|
| | : - |
| Transmitting power | : 10 mW |
| Operating range | : - |
| Power supply transmitter | : 2 x 1.5 V batt. AA size |
| Width transmitter | : 65 mm |
| Height transmitter | : 110 mm |
| Depth transmitter | : 25 mm |
| Weight transmitter | : 76 g |
| Connections transmitter | : 1 x 3-pole mini XLR |
| Specifications receiver | : - |
| Audio signal receiver | : - |
| Power supply receiver | : - |
| Width receiver | : - |
| Height receiver | : - |
| Depth receiver | : - |
| Weight receiver | : - |
| Connections receiver | : - |