-

Tekniset tiedot:

Peak output power	: 2 x 100 W
Power rating	: 100 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 2 x 50 W
Power rating at 8 Ohm	: 2 x 30 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: 125Â mV/10Â kOhm (line)1.3 mV/600 Ohm (mic)
Attenuation factor	: -
Frequency range	: 20-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: ± 12 dB/30 Hz
Equalizer midrange	: ± 12 dB/1 kHz (voice only)
Equalizer treble	: ± 12 dB/12 kHz
S/N ratio	: ? 60 dB
Crosstalk attenuation	: -
THD	: -
Mains voltage	: ∼ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 220 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 432 mm
Height	: 52 mm

Depth	: 275 mm

Rack spaces, RS	:	1
Weight	:	3.5 kg
Connections	:	3 x RCA L/R (line),2 x 6.3 mm jack, bal. (mic), 2 x RCA L/R (master),1 x RCA L/R (rec.),1 x plug-in screw terminal (mute),4 x spring-load. speaker term. (speakers)