

## STA-200D - Amplifier



Stereo class D PA amplifier, 250 W

- 5 switchable line inputs
- Silent operation due to fanless cooling concept
- High power reserves due to generously dimensioned toroidal core transformer
- High-efficiency power amplifiers
- 3.5 mm stereo jack connection with switchable sensitivity on the front panel
- 4 x RCA input
- 2 x SPEAKER output
- 4 x terminal strip output
- 2 level controls
- Protected against short circuit, overvoltage and overtemperature
- LEDs for indicating power, overload (clip), protect and overheating
- Super slimline and robust design, 1 RS

## Tekniset tiedot:

|  |   |
|--|---|
| Peak output power                            | : 300 W   |
| Power rating                                 | : 250 W   |
| Power rating at 2 Ohm                        | : -   |
| Power rating at 4 Ohm                        | : 2 x 125 W   |
| Power rating at 8 Ohm                        | : 2 x 75 W  |
| Power rating at 16 Ohm                       | : -   |
| Power rating at 100 V                        | : -   |
| Power rating with 4 Ohm<br>bridged operation | : -   |
| Power rating with 8 Ohm<br>bridged operation | : -   |
| Output impedance                             | : -   |
| Channels                                     | : 2   |
| Zones  | : -   |
| Inputs                                       | : 1 $\hat{A}$ V/23 $\hat{A}$ kOhm (RCA), 90 mV-1 V (jack) |
| Attenuation factor                           | : -   |
| Frequency range                              | : 20-20,000 Hz  |
| Crossover network                            | : -   |
| Crossover frequency                          | : -   |
| Integrated limiter                           | : -   |
| Equalizer bass                               | : -   |
| Equalizer midrange                           | : -   |
| Equalizer treble                             | : -   |
| S/N ratio                                    | : ? 100 dBA   |
| Crosstalk attenuation                        | : ? 56 dB   |
| THD  | : < 0.05%   |
| Mains voltage                                | : $\sim$ 230 V  |
| Mains frequency                              | : 50 Hz   |
| Power consumption, operation                 | : 350 VA  |
| Power consumption, standby                   | : -   |
| Standby current                              | : -   |
| Operating voltage (possible<br>alternative)  | : -   |
| Power supply (possible<br>alternative)       | : -   |
| Admiss. ambient temp.                        | : 0-40 $^{\circ}$ C                                       |
| Width  | : 483 mm  |
| Height                                       | : 44 mm   |

Depth

: 268 mm





|                 |  |
|-----------------|--|
| Rack spaces, RS | : 1  |
| Weight          | : 5 kg   |
| Connections     | : 1 x 3.5 mm stereo jack<br>4 x RCA L/R<br>1 x SPEAKER L/R<br>1 x spring-load. speaker term. L/R |