

## ETS-210TW/WS - PA Speaker Column



Slim Design, Weatherproof Version  
PA column speakers,  
in extruded aluminium cabinets.

- Weatherproof and hose-proof
- 100 V line technique
- 2-way version (with additional integrated tweeters for a clearly improved sound)
- Connection cable with 5-step power taps
- 2 x M6 threaded bushing
- Aluminium front grille
- Supplied with mounting brackets

## Tekniset tiedot:

|                                |                        |
|--------------------------------|------------------------|
| Active/passive                 | : passive              |
| Transmission method            | : 100 V                |
| Total output power             | : -                    |
| Power rating (RMS)             | : -                    |
| Total power rating             | : -                    |
| Power rating (RMS)             | : 10/5/2.5/1.25/0.63 W |
| Impedance                      | : -                    |
| Frequency range                | : 170-20,000 Hz        |
| THD                            | : -                    |
| S/N ratio                      | : -                    |
| Input signal                   | : -                    |
| System                         | : 2-way                |
| Full range speaker             | : -                    |
| Bass speaker                   | : -                    |
| Midrange speaker               | : -                    |
| Tweeter                        | : -                    |
| Number of speakers             | : 2+1                  |
| Speaker size                   | : -                    |
| Sensitivity                    | : 86 dB/W/m            |
| Max. rated SPL                 | : -                    |
| Radiation angle, horizontal    | : -                    |
| Radiation angle, vertical      | : -                    |
| Features                       | : -                    |
| Housing material               | : aluminium            |
| Colour                         | : white                |
| Mounting device                | : mounting bracket     |
| Protected against ball rebound | : -                    |
| Protection class               | : IP66                 |
| Admiss. ambient temp.          | : -20 °C to +50 °C     |
| Power supply                   | : -                    |
| Dimensions                     | : 80 x 280 x 70 mm     |
| Width                          | : 80 mm                |
| Height                         | : 280 mm               |
| Depth                          | : 70 mm                |
| Weight                         | : 1 kg                 |



|                        |     |
|------------------------|-----|
| Inputs                 | : - |
| Outputs                | : - |
| Replacement voice coil | : - |
| Other features         | : - |
| Accessories            | : - |