

# CC-142 - Compact Connecting Terminal



Connecting terminal from WAGO

- 2-conductor terminal with operating levers
- Individually combinable wires and cross sections from 0.14 to 4 mm<sup>2</sup>
- Power rating: 450 V/32 A
- Continuous operating temperature: up to 85 °C
- Correct position of the conductor and stripping length can be visually checked due to transparent housing
- Two test slots for any standard test prod
- Of very compact size, thus, ideally suited for application in confined spaces

## Tekniset tiedot:

|                              |   |
|------------------------------|---|
| Description                  | : connecting terminal   |
| Type                         | : WAGO  |
| Quantity                     | : 1   |
| Features                     | : operating levers  |
| Colour/colour coding         | : transparent   |
| Power rating                 | : 450 V/32 A  |
| Insulating resistance        | : -   |
| Dielectric strength          | : 4 kV  |
| Certification                | : UL, ABS, LR   |
| Pole number                  | : 2   |
| Cable inlet                  | : AWG 24-12   |
| Suitable cable cross section | : flexible conductors: 0.14-4 mm <sup>2</sup> rigid conductors: up to 0.2-4 mm <sup>2</sup> |
| Connection                   | : 2-conductor terminal with operating levers  |
| Strain relief                | : -   |
| Cable bending protection     | : -   |
| Stereo                       | : -   |
| Mono                         | : -   |
| Switches                     | : -   |
| Material                     | : -   |
| Central fixing               | : -   |
| Contact type                 | : -   |
| No. of contacts              | : -   |
| Contact width                | : -   |
| Contact distance             | : -   |
| Admiss. ambient temp.        | : 85 °C   |
| Dimensions                   | : 13.1 x 8.3 x 18.6 mm  |
| Diameter                     | : -   |
| Length                       | : -   |
| Weight                       | : 1.6 g   |
| Other features               | : -   |