


PA-704 - PA Amplifier

100V 4Ω 8Ω 16Ω new



Mono PA mixing amplifier

- 1 x 35 W
- Silent operation due to fanless cooling concept
- 2 low-impedance microphone inputs
- 1 aux input, 1 phono input
- Speaker outputs via screw terminals
- Input and output level controls
- 2-way tone control for the output
- Connection for a microphone talk button to switch off the other sources during announcements
- Mains operation and 12-24 V emergency power operation

Tekniset tiedot:

Peak output power	: 70 W
Power rating	: 35 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: -
bridged operation	
Output impedance	: -
Channels	: 4
Zones	: -
Inputs	: 5 mV (mic), 210 mV (aux), 5 mV (phono)

Attenuation factor	: -
Frequency range	: 100-18,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: ± 10 dB/150 Hz
Equalizer midrange	: -
Equalizer treble	: ± 10 dB/6 kHz
S/N ratio	: ? 55 dB
Crosstalk attenuation	: -
THD	: < 1%

Phantom power	: -
Mains voltage	: \approx 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 100 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: DC 12-24 V
Power supply (possible alternative)	: DC 2.5 A
Admiss. ambient temp.	: 0-40 °C

Width
Height

: 320 mm
: 85 mm





Depth	: 230 mm
Rack spaces, RS	: -
Weight	: 4.97 kg
Connections	: 2 x 6.3 mm jack (mic), 1 x RCA L/R (aux), 1 x RCA L/R (phono), connecting terminals (speakers)