

PA-302 - PA Amplifier



Mono PA mixing amplifier,
14 W.

- 1 microphone input and 1 line input, adjustable
- 2 speaker outputs, switchable
- Built-in speaker
- Can also be operated as an intercom system
- Supplied with hand-held push-to-talk microphone
- Siren and fog horn, automatic fog horn
- Metal housing
- Supplied with mounting brackets
- 12/24 V battery operation, automatic switching

Tekniset tiedot:

| | |
|--|-----------------------------|
| Peak output power | : 20 W |
| Power rating | : 14 W |
| Power rating at 2 Ohm | : - |
| Power rating at 4 Ohm | : - |
| Power rating at 8 Ohm | : - |
| Power rating at 16 Ohm | : - |
| Power rating at 100 V | : - |
| Power rating with 4 Ohm | : - |
| bridged operation | |
| Power rating with 8 Ohm | : - |
| bridged operation | |
| Output impedance | : - |
| Channels | : 2 |
| Zones | : - |
| Inputs | : 3Â mV (mic), 50 mV (line) |
| Attenuation factor | : - |
| Frequency range | : 20-20,000 Hz |
| Crossover network | : - |
| Crossover frequency | : - |
| Integrated limiter | : - |
| Equalizer bass | : - |
| Equalizer midrange | : - |
| Equalizer treble | : - |
| S/N ratio | : 65 dB |
| Crosstalk attenuation | : - |
| THD | : < 0.5% |
| Mains voltage | : - |
| Mains frequency | : - |
| Power consumption, operation | : - |
| Power consumption, standby | : - |
| Standby current | : - |
| Operating voltage (possible alternative) | : - |
| Power supply (possible alternative) | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Width | : 175 mm |
| Height | : 60 mm |

Depth

: 170 mm





| | |
|-----------------|---|
| Rack spaces, RS | : - |
| Weight | : 1.4 kg |
| Connections | : 1 x 6.3 mm jack (mic input), 1 x RCA (line input), 2 x 2-pole plug-in screw terminal (speakers), 1 x 3-pole plug-in screw terminal with jumper (external speaker) |