

---

-

## Tekniset tiedot:

Peak output power	: -
Power rating	: 15 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: -
bridged operation	
Output impedance	: 4-16 Ohm
Channels	: 3
Zones	: -
Inputs	: 3Â mV (mic),500 mV/3 mV (aux/phono)
Attenuation factor	: -
Frequency range	: 80-18,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 75 dB
Crosstalk attenuation	: -
THD	: < 1%
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 60 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: DC 12 V
Power supply (possible alternative)	: DC 2 A
Admiss. ambient temp.	: 0-40 °C
Width	: 240 mm
Height	: 75 mm

Depth

: 230 mm

---

Rack spaces, RS	: -
Weight	: 3.2 kg
Connections	: 2 x 6.3 mm jack (mic), 1 x RCA L/R (aux/phono), screw terminals (speakers)