
-

Tekniset tiedot:

Peak output power	: -
Power rating	: 120 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: -
bridged operation	
Output impedance	: -
Channels	: 1
Zones	: 1
Inputs	: 5-8 mV/600 Ohm (mic 1-3), 150-470 mV/10 kOhm (line, unbal.),
Attenuation factor	: -
Frequency range	: 60-15,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: yes
Equalizer midrange	: -
Equalizer treble	: yes
S/N ratio	: 72 dB (mic) 85 dB (aux)
Crosstalk attenuation	: -
THD	: < 0.5%
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 250 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: DC 24 V
Power supply (possible alternative)	: 8.4 A
Admiss. ambient temp.	: 0-40 °C
Width	: 320 mm

Height : 95 mm
Depth : 245 mm

Rack spaces, RS	: -
Weight	: 5 kg
Connections	: 1 x XLR (mic 1), 2 x 6.3 mm jack (mic 2-3/line 1-2), 2 x RCA L/R (line 3-4), 2 x RCA (master out), 1 x IEC (FM), screw terminals (emergency, MOH, DC 24 V, speakers)