-

Tekniset tiedot:

Peak output power	: 1,200 W
Power rating	: 1,000 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 2 x 500 W
Power rating at 8 Ohm	: 2 x 280 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: 1 x 1,000 W
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: 1.2Â V/24Â kOhm (XLR, bal.)
Attenuation factor	: -
Frequency range	: 20-20,000 Hz
Crossover network	: DSP
Crossover frequency	: -
Integrated limiter	: yes
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 119 dBA
Crosstalk attenuation	: -
THD	: < 0.05%
Mains voltage	: ∼ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 1,160 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm
Height	: 89 mm
Depth	: 335 mm

Rack spaces, RS	:	2
Weight	:	5.18 kg
Connections	:	1 x 3-pole XLR L/R1 x 3-pole XLR (subwoofer)1 x NEUTRIK POWERCON1 x NEUTRIK SPEAKON L/R 1 x NEUTRIK SPEAKON bridgedUSBEthernet (Cat. 5)