

## KU-916T - Horn Driver



Weatherproof horn driver

- 100 V line technique
- Protected against powerful water jets
- Power selector switch
- 3.5 cm (1 1/4") mounting flange
- 60 cm connection cable

## Tekniset tiedot:

|                                |                          |
|--------------------------------|--------------------------|
| Active/passive                 | : passive                |
| Transmission method            | : 100 V                  |
| Total output power             | : -                      |
| Power rating (RMS)             | : -                      |
| Total power rating             | : 60 W                   |
| Power rating (RMS)             | : 60/50/40/30/20/10 W    |
| Impedance                      | : -                      |
| Frequency range                | : 160-7,000 Hz           |
| THD                            | : -                      |
| S/N ratio                      | : -                      |
| Input signal                   | : -                      |
| System                         | : -                      |
| Full range speaker             | : -                      |
| Bass speaker                   | : -                      |
| Midrange speaker               | : -                      |
| Tweeter                        | : -                      |
| Number of speakers             | : 1                      |
| Speaker size                   | : -                      |
| Sensitivity                    | : 113 dB/W/m             |
| Max. rated SPL                 | : -                      |
| Radiation angle, horizontal    | : -                      |
| Radiation angle, vertical      | : -                      |
| Features                       | : power selector switch  |
| Housing material               | : metal                  |
| Colour                         | : dark grey              |
| Mounting device                | : 3.5 cm mounting flange |
| Protected against ball rebound | : -                      |
| Protection class               | : IP66                   |
| Admiss. ambient temp.          | : -20 °C to +50 °C       |
| Power supply                   | : -                      |
| Dimensions                     | : 150 mm x 158 mm        |
| Width                          | : 150 mm                 |
| Height                         | : -                      |
| Depth                          | : 158 mm                 |
| Weight                         | : 2.75 kg                |



---

|                        |                |
|------------------------|----------------|
| Inputs                 | : -            |
| Outputs                | : -            |
| Replacement voice coil | : KU-916T/VC   |
| Other features         | : weatherproof |
| <b>Accessories</b>     | : -            |