
-

Tekniset tiedot:

Active/passive	: active
Transmission method	: Cables
Total output power	: 300 W
Power rating (RMS)	: 175 W
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 45-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: 240 mV (line, XLR, bal.), 950 mV (line, RCA), 10 mV (mic, bal.)
System	: 15/2 full range
Full range speaker	: -
Bass speaker	: 38 cm (15") bass speaker
Midrange speaker	: -
Tweeter	: 25 mm (1", 44 mm voice coil) horn tweeter
Number of speakers	: 2
Speaker size	: 38 cm (15")
Sensitivity	: 96 dB/W/m
Max. rated SPL	: 119 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: black
Mounting device	: stand sleeve
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: ∿ 230 V/50 Hz/370 VA
Dimensions	: 447 x 685 x 355 mm
Width	: 447 mm
Height	: 685 mm
Depth	: 355 mm
Weight	: 22 kg

Inputs	: XLR and RCA L/R (line)2 x XLR (mic)2 x 6.3 mm jack (mic)
Outputs	: XLR (par. line out), 6.3 mm jack (par. line out)
Replacement voice coil	: PAB-115/VC
Other features	: 2-band EQ ± 12 dB, integr. limiter
Accessories	: PAB-115BAG