
-

Tekniset tiedot:

Active/passive	: passive
Transmission method	: Cables
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 700 W
Power rating (RMS)	: 350 W
Impedance	: 8 Ohm
Frequency range	: 45-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way bass-reflex
Full range speaker	: -
Bass speaker	: 38 cm (15", 75 mm voice coil)
Midrange speaker	: -
Tweeter	: 25 mm (1")dyn. mid-high range speaker(44 mm voice coil)
Number of speakers	: 2
Speaker size	: 38 cm (15")
Sensitivity	: 99 dB/W/m
Max. rated SPL	: 124 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: MDF, plywood
Colour	: black
Mounting device	: M8 threaded inserts, stand sleeve
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 470 x 770 x 440 mm
Width	: 470 mm
Height	: 770 mm
Depth	: 440 mm
Weight	: 31.8 kg

Inputs	: 1 x NEUTRIK SPEAKON
Outputs	: 1 x NEUTRIK SPEAKON par. out
Replacement voice coil	: PAB-115/VC
Other features	: -
Accessories	: -