


SP-10/4S - Mini Loudspeaker



Universal speaker, 15 W, 4 Ohm

- Magnetic shielding
- Wide bandwidth speaker of high power capability
- Reproduction from approx. 80 Hz on

Tekniset tiedot:

Impedance (Z)	: 4 Ohm
Transmission method	: -
Frequency range	: f3-8,000 Hz
Resonant frequency (fs)	: -
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 15 W
Peak music power output (MAX)	: 25 W
Sensitivity	: 88 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: Å~ 77.5 mm
Mounting cutout	: Å~ 103 mm
Mounting depth	: 63.2 mm
Mounting hole diameter	: Å~ 114.5 mm
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: 105 x 105 x 64 mm
Outside diameter	: -
Width	: 105 mm

Height	: 105 mm
Depth	: 64 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.59 kg
Packing unit	: 1
Type of speaker	: 4"