



SP-100/8 - Loudspeaker



Hi-fi bass-midrange speaker, 30 W, 8 Ohm

- Robust paper cone
- High-quality aluminium coil
- Drilled pole core
- Rubber surround
- Excellent radiation and transient response

Tekniset tiedot:

Impedance (Z)	: 8 Ohm
Transmission method	: -
Frequency range	: f3-7,000 Hz
Resonant frequency (fs)	: 61 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 30 W
Peak music power output (MAX)	: 60 W
Sensitivity	: 88 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: 1.23 mm/N
Moving mass (Mms)	: 5.5 g
Mech. Q factor (Qms)	: 2.28
Electr. Q factor (Qes)	: 0.44
Total Q factor (Qts)	: 0.37
Equivalent volume (Vas)	: 4.7 l
DC resistance (Re)	: 6.5 Ohm
Force factor (BxL)	: 5.50 Tm
Voice coil induct. (Le)	: 0.4 mH
Voice coil diameter	: $\varnothing \sim 25$ mm
Voice coil former	: aluminium
Linear excursion (X _{MAX})	: ± 2.5 mm
Eff. cone area (Sd)	: 52 cm ²
Magnet weight	: 280 g
Magnet diameter	: $\varnothing \sim 80$ mm
Mounting cutout	: $\varnothing \sim 103$ mm
Mounting depth	: 62.2 mm
Mounting hole diameter	: $\varnothing \sim 114.5$ mm
Hole spacing X-axis	: 81 mm
Hole spacing Y-axis	: 81 mm
Dimensions	: 106 x 106 x 63 mm
Outside diameter	: $\varnothing \sim 127$ mm
Width	: 106 mm



Height	: 106 mm
Depth	: 63 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.79 kg
Packing unit	: 1
Type of speaker	: 4"