

## WALL-05DTM/WS - 2-Way Dante Speaker Cabinet



Active speaker with integrated Dante(r) module

- 2-way system
- 13 cm (5") bass-midrange speaker and 13 mm (½") tweeter
- Mounting bracket for pivoting and tilting
- Power supply via PoE (Power over Ethernet) or via optional power supply (19 V/2.5 A)

System requirements Dante(r): Windows 7/8.1/10/11 or MacOS 10.9.5/10.10.5/10.11

The brand Dante(r) as well as the Dante(r) software which may have been integrated into these products are licenced by Audinate Pty Ltd.

## Tekniset tiedot:

|                                |                        |
|--------------------------------|------------------------|
| Active/passive                 | : active               |
| Transmission technology        | : Dante <sup>(r)</sup> |
| Total output power             | : -                    |
| Power rating (RMS)             | : 30 W                 |
| Total power rating             | : -                    |
| Power rating (RMS)             | : -                    |
| Impedance                      | : -                    |
| Frequency range                | : 62-20,000 Hz         |
| THD                            | : -                    |
| S/N ratio                      | : -                    |
| Input signal                   | : -                    |
| System                         | :                      |
| Full range speaker             | : -                    |
| Bass speaker                   | :                      |
| Midrange speaker               | : -                    |
| Tweeter                        | :                      |
| Number of speakers             | : 2                    |
| Speaker size                   | : 13 cm                |
| SPL                            | : 89 dB/W/m            |
| Max. rated SPL                 | : 105 dB               |
| Beam angle                     | : -                    |
| Radiation angle, horizontal    | : -                    |
| Radiation angle, vertical      | : -                    |
| Features                       | : -                    |
| Housing material               | :                      |
| Colour                         | :                      |
| Mounting device                | :                      |
| Protected against ball rebound | : -                    |
| Protection class               | : -                    |
| Admiss. ambient temp.          | : 0-40 °C              |
| Power supply                   | :                      |
| Dimensions                     | :                      |
| Width                          | : 163 mm               |
| Height                         | : 252 mm               |
| Depth                          | : 165 mm               |



|                                |           |
|--------------------------------|-----------|
| Weight                         | : 2.12 kg |
| Inputs                         | :         |
| Outputs                        | :         |
| Replacement voice coil         | : -       |
| Other features                 | : -       |
| Accessories                    | : -       |
| Packing dimensions (W x H x L) | :         |
| Gross weight                   | : 2.72 kg |
| Net weight                     | : 2.44 kg |