

WALL-05SET/WS - Active Cabinets



Active 2-way stereo speaker system, 2 x 30 W

- Set consists of one active and one passive speaker system. Connection of the passive system to the active system via screw terminal strip
- Active speaker system with integrated 2-channel amplifier
- Stereo RCA input or balanced input L/R via screw terminal strip
- Volume control and 2-way tone control
- Auto standby
- 13 cm (5") bass speaker system and dome tweeter
- Stylish white plastic cabinet
- Mounting bracket for pivoting and tilting

Tekniset tiedot:

| | |
|--------------------------------|--|
| Active/passive | : active/passive |
| Transmission method | : cable |
| Total output power | : 2 x 50 W |
| Power rating (RMS) | : 2 x 30 W |
| Total power rating | : - |
| Power rating (RMS) | : - |
| Impedance | : - |
| Frequency range | : 80-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : 500 mV/20Â kOhm (unbal.) 660 mV/40 kOhm (bal.) |
| System | : 2-way |
| Full range speaker | : - |
| Bass speaker | : 13 cm (5") bass speaker |
| Midrange speaker | : - |
| Tweeter | : dome tweeter |
| Number of speakers | : 2 |
| Speaker size | : 13 cm (5") |
| Sensitivity | : 89 dB/W/m |
| Max. rated SPL | : 104 dB |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : plastic |
| Colour | : white |
| Mounting device | : mounting bracket |
| Protected against ball rebound | : - |
| Protection class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : ∿ 230 V/50 Hz/100 VA |
| Dimensions | : 163 x 252 x 203Â mm (with bracket) |
| Width | : 163 mm |
| Height | : 252 mm |
| Depth | : 203 mm |
| Weight | : 5.5Â kg (pair) |



| | |
|------------------------|--|
| Inputs | : 1 x RCA L/R (unbalanced) 1 x terminal L/R (balanced) spr.-load speak. term. (passive speaker system) spr.-load speak. term. |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : pair |
| Accessories | : - |