
-

Tekniset tiedot:

Active/passive	: active/passive
Transmission method	: -
Total output power	: 2 x 25 W
Power rating (RMS)	: 2 x 15 W
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 45-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: 400 mV/10 kOhm
System	: 2-way
Full range speaker	: -
Bass speaker	: 16 cm (6½") bass speaker
Midrange speaker	: -
Tweeter	: dome tweeter
Number of speakers	: 2
Speaker size	: 16 cm (6.5")
Sensitivity	: 89 dB/W/m
Max. rated SPL	: 100 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: ∿ 230 V/50 Hz/75 VA
Dimensions	: 220 x 293 x 170 mm
Width	: 220 mm
Height	: 293 mm
Depth	: 170 mm
Weight	: 8 kg (pair)

Inputs	: 1 x RCA L/R (active speaker system only) spring-load. speaker term. (link, both speaker systems)
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -