


MKA-50SET/SW - Active Cabinets



Active 2-way stereo speaker systems, 2 x 20 W

- Set consists of an active and a passive speaker system. Connection of the passive system to the active system via spring-loaded speaker terminals
- Active speaker system with integrated 2-channel amplifier and power supply
- Speakers with magnetic shielding
- Auto-standby function
- Volume control and 2-way tone control

Tekniset tiedot:

| | |
|--------------------------------|------------------------------------|
| Active/passive | : active/passive |
| Transmission method | : - |
| Total output power | : 2 x 40 W |
| Power rating (RMS) | : 2 x 20 W |
| Total power rating | : - |
| Power rating (RMS) | : - |
| Impedance | : - |
| Frequency range | : 60-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : 420 mV/24 kOhm |
| System | : 2-way |
| Full range speaker | : - |
| Bass speaker | : 13 cm (5") bass-midrange speaker |
| Midrange speaker | : - |
| Tweeter | : 2.5 cm (1") tweeter |
| Number of speakers | : 2 |
| Speaker size | : 13 cm (5") |
| Sensitivity | : 89 dB/W/m |
| Max. rated SPL | : 102 dB |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : plastic |
| Colour | : black |
| Mounting device | : mounting bracket |
| Protected against ball rebound | : - |
| Protection class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : ∿ 230 V/50 Hz/110 VA |
| Dimensions | : 180 x 250 x 160 mm |
| Width | : 180 mm |
| Height | : 250 mm |
| Depth | : 160 mm |
| Weight | : 5.9Â kg (pair) |



| | |
|------------------------|--|
| Inputs | : 1 x RCA L/R (active speak. system only) 1 x 3.5 mm jack screw terminals (both speaker systems) |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : pair |
| Accessories | : - |