

## HSE-821SX - Headworn Microphone



Replacement electret headband microphone

- Suitable for vocal and speech applications
- Microphone cartridge with cardioid polar pattern
- Gooseneck cartridge arm
- 1.3 m connection cable with 3.5 mm plug, with latching device
- Operation via a pocket transmitter of the series TXS-820SX, TXS-822SX, TXS-820LT or TXS-822LT
- Microphone windshield

## Tekniset tiedot:

|                         |                       |
|-------------------------|-----------------------|
| Description             | : headband microphone |
| Version                 | : -                   |
| Transmission method     | : cable               |
| Polar pattern           | : cardioid            |
| System                  | : electret            |
| Carrier frequency range | : -                   |
| Transmitting power      | : -                   |
| Power supply            | : -                   |
| Operating time          | : -                   |
| Audio frequency range   | : 80-12,000 Hz        |
| Nominal impedance       | : 680 Ohm             |
| Sensitivity             | : 5.6 mV/Pa           |
| S/N ratio               | : 60 dB               |
| Max. sound pressure     | : 110 dB              |
| Power supply            | : 1.5-3 V             |
| Gooseneck length        | : -                   |
| Housing material        | : -                   |
| Admiss. ambient temp.   | : 0-40 °C             |
| Dimensions              | : -                   |
| Weight                  | : 60 g                |
| Cable                   | : 1.3 m               |
| Connection              | : 3.5 mm plug         |