

## SP-6/4SQ - Mini Loudspeaker



Universal speaker, 3 W, 4 Ohm

- For standard applications in the miniature speaker range
- Sound pressure from approx. 280 Hz on

## Tekniset tiedot:

|   |                   |
|---|-------------------|
| Impedance (Z)                             | : 4 Ohm           |
| Transmission method                       | : -               |
| Frequency range                           | : f3-16,000 Hz    |
| Resonant frequency (fs)                   | : -               |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | : -               |
| Power rating (RMS)                        | : 3 W             |
| Peak music power output (MAX)             | : 5 W             |
| Sensitivity                               | : -               |
| Max. rated SPL                            | : -               |
| Max. voltage                              | : -               |
| Radiation angle, horizontal               | : -               |
| Radiation angle, vertical                 | : -               |
| Suspension compl. (Cms)                   | : -               |
| Moving mass (Mms)                         | : -               |
| Mech. Q factor (Qms)                      | : -               |
| Electr. Q factor (Qes)                    | : -               |
| Total Q factor (Qts)                      | : -               |
| Equivalent volume (Vas)                   | : -               |
| DC resistance (Re)                        | : -               |
| Force factor (BxL)                        | : -               |
| Voice coil induct. (Le)                   | : -               |
| Voice coil diameter                       | : -               |
| Voice coil former                         | : -               |
| Linear excursion (X <sub>MAX</sub> )      | : -               |
| Eff. cone area (Sd)                       | : -               |
| Magnet weight                             | : -               |
| Magnet diameter                           | : Å~ 40 mm        |
| Mounting cutout                           | : Å~ 51 mm        |
| Mounting depth                            | : 25.2 mm         |
| Mounting hole diameter                    | : Å~ 64 mm        |
| Hole spacing X-axis                       | : -               |
| Hole spacing Y-axis                       | : -               |
| Dimensions                                | : 59 x 59 x 26 mm |
| Outside diameter                          | : -               |
| Width                                     | : 59 mm           |



|                       |           |
|-----------------------|-----------|
| Height                | : 59 mm   |
| Depth                 | : 26 mm   |
| Protective class      | : -       |
| Admiss. ambient temp. | : 0-40 °C |
| Weight                | : 83 g    |
| Packing unit          | : 1       |
| Type of speaker       | : 2"      |