

CAT-7100A - CAT7 Cable

100 m



Cat. 7A installation cable, multiple shielding, S/FTP

- 100 m, shrink-wrapped coil
- 10 Gbps, 1,000 MHz
- Conductor pairs in metal foil (PiMF), complies with EIA/TIA 568
- Overall braided shield
- Cable specification: 4x2xAWG 23
- Outside diameter: Ø 7.50 mm

Tekniset tiedot:

| | |
|------------------------|---------------------------------|
| Intended use | : 10GBASE-T Ethernet |
| Connectors | : - |
| Cable specification | : 4x2xAWG 23/1 CU, S/FTP |
| Length | : 100 m |
| Colour | : orange |
| Cable diameter | : \varnothing 7.5 mm |
| Metre marking | : - |
| Minimum bending radius | : 4xD |
| Shielding | : S/FTP |
| Shielding value | : - |
| Impedance | : 100 Ohm @100 MHz |
| Attenuation | : ? 85 dB |
| Capacitance | : - |
| Power rating | : Cat7 _A , 1,000 MHz |
| Rated current | : - |
| Internal conductor | : - |
| No. of cores | : 4 x 2 pair |
| Material | : copper |
| Packaging | : coil, shrink-wrapped |
| Weight | : 6 kg |
| Position | : - |
| Special feature | : - |
| Other features | : - |