

ATS-10PS - Charger



16-channel Mono PLL Audio Transmission System, 863-865 MHz

- Suitable as a tour guide system and for any other application in which a certain audio source or voice source is to be distributed to one or more receivers
- Wireless transmissions of audio signals with one transmitter and one receiver are also possible
- Due to the small frequency spacing in this free frequency range, a simultaneous operation of not more than two transmitters is recommended (with optimum conditions, up to 7 transmitters max. are possible)
- Licence-free in the EU

Automatic quick-charge station,

for simultaneously charging rech. batteries of two devices from the ATS-10 series.

- Average charging time, depending on capacity and condition of the rechargeable batteries used: approx. 3-4 hours, e.g. for 1,300 mAh rech. batteries
- Operating LEDs for "charging" and "charging completed"
- Including plug-in power supply

Tekniset tiedot:

Description	: quick charging station
Nominal value	: 2 devices
Type	: automatic
Colour	: black
Material	: -
Suitable for	: ATS-10R, ATS-10TM
Power supply	: via encl. plug-in power supply
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 232 x 51 x 140 mm
Length	: -
Mounting dimensions	: -
Weight	: 350 g
Connections	: -
Other features	: -
Packing unit	: 1