

HSE-40/SK - Headworn Microphone



Ultra-light miniature earband microphone

- Back electret microphone cartridge
- Omnidirectional polar pattern
- 3-pole mini XLR inline jack
- Unobtrusive design with earlobe support
- Silicone band to perfectly fit ears of all shapes and sizes
- Compatible with pocket transmitters TXS-...HSE with 3-pole mini XLR connection
- External power supply, e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Microphone windshield

Tekniset tiedot:

| | |
|-------------------------|-----------------------|
| Description | : headband microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : omnidir. |
| System | : back electret |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : - |
| Operating time | : - |
| Audio frequency range | : 20-20,000 Hz |
| Nominal impedance | : 2 kOhm |
| Sensitivity | : 7.9 mV/Pa |
| S/N ratio | : - |
| Max. sound pressure | : 130 dB |
| Power supply | : DC 1.5-9 V |
| Gooseneck length | : - |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : - |
| Weight | : 14 g |
| Cable | : - |
| Connection | : 3-pole mini XLR |