


DT-99 - HiFi Dome Tweeter


**FERRO
FLUID**

**80
W_{RMS}**

**25
mm**



DT-99



Hi-fi dome tweeter, 40 W, 8 Ohm

- Pure silk cone
- Excellent radiation
- Very typical sound pressure curve
- For replacement purposes and hi-fi applications

Tekniset tiedot:

Impedance (Z)	: 8 Ohm
Transmission method	: -
Frequency range	: fx-18,000 Hz
Resonant frequency (fs)	: 1,500 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: 2,500 Hz
Power rating (RMS)	: 40 W
Peak music power output (MAX)	: 80 W
Sensitivity	: 93 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: $\tilde{\text{A}}$ 25 mm
Voice coil former	: -
Linear excursion (X_{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: $\tilde{\text{A}}$ 70 mm
Mounting cutout	: $\tilde{\text{A}}$ 85 mm
Mounting depth	: 34 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: $\tilde{\text{A}}$ 99.5 x 34 mm
Outside diameter	: $\tilde{\text{A}}$ 99.5 mm
Width	: $\tilde{\text{A}}$ 99.5 mm



Height	: -
Depth	: 34 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.51 kg
Packing unit	: 1
Type of speaker	: -