

## TXA-800R - Receiver



### **Professional 16-channel Mono PLL Audio Transmission System, 863,1-864,9 MHz, with Extensive Accessories**

- Compatible with portable amplifier systems of the TXA-800 and TXA-1020 series
- Can be combined with the TXA-800 and TXA-1020 series, but also suitable as a tour guide system and for any other application in which a certain audio source or voice source is to be distributed to one or more receivers
- Can be combined with transmitters and receivers of the ATS-16 series
- Simultaneous operation of up to 4 transmitters with different frequencies (dep. on distance of transmitters, stationary RF sources of interference and other local conditions)
- Licence-free in the EU

### **16-channel PLL receiver**

- Matching the transmitters TXA-800ST, ATS-16T and portable amplifier system TXA-802CD with integrated wireless transmitter
- 16 selectable UHF frequencies (863.1-864.9 MHz)
- Adjustable headphone output
- Audio line mono output via 3.5 mm stereo jack
- Line output level adjustable in 3 steps
- Backlit LCD for indicating channel/frequency and battery status
- Metal housing
- Power supply via 2 x 1.5 V battery AA size or NiMH rech. battery (not supplied)
- Scope of delivery includes earphones with rubber ear hook
- Belt clip



**Licence-free in the EU.** Matching microphone transmitter TXA-800HT is available at option.

## Tekniset tiedot:

### General information

	: -
Description	: pocket receiver
Carrier frequency range	: 863.1-864.9 MHz
Audio frequency range	: -
Channels	: 1
THD	: -
Dynamic range	: -
RF S/N ratio	: -
Operating time	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: -
Total weight	: -
Connections	: -
Specifications transmitter	: -
Transmitting power	: -
Operating range	: -
Power supply transmitter	: -
Width transmitter	: -
Height transmitter	: -
Depth transmitter	: -
Weight transmitter	: -
Connections transmitter	: -

### Specifications receiver

Audio signal receiver	: -
Power supply receiver	: 2 x 1.5 V batt. AA size
Width receiver	: 64 mm
Height receiver	: 175 mm
Depth receiver	: 37 mm
Weight receiver	: 200 g
Connections receiver	: 1 x 3.5 mm mono jack (line in), 1 x 3.5 mm stereo jack (headphones)