-

Tekniset tiedot:

Active/passive	:	passive
Transmission method	:	-
Total output power	:	-
Power rating (RMS)	:	-
Total power rating	:	100 W
Power rating (RMS)	:	50 W
Impedance	:	8 Ohm
Frequency range	:	70-20,000 Hz
THD	:	-
S/N ratio	:	-
Input signal	:	-
System	:	2-way
Full range speaker	:	-
Bass speaker	:	16 cm (6") bass-midrange speaker
Midrange speaker	:	-
Tweeter	:	25 mm (1") dome tweeter
Number of speakers	:	2
Speaker size	:	6"
Sensitivity	:	90 dB/W/m
Max. rated SPL	:	106 dB
Radiation angle, horizontal	:	-
Radiation angle, vertical	:	-
Features	:	-
Housing material	:	plastic
Colour	:	black
Mounting device	:	mounting bracket
Protected against ball rebound	:	-
Protection class	:	IP65
Admiss. ambient temp.	:	0-40 °C
Power supply	:	-
Dimensions	:	196 x 303 x 250 mm (with bracket)
Width	:	196 mm
Height	:	303 mm
Depth	:	250 mm
Weight	:	3.05 kg

Inputs	: spring-load. speaker term.
Outputs	: -
Replacement voice coil	: -
Other features	: for pivoting and tilting
Accessories	: -