

## EDL-435/WS - PA Loudspeaker



High-quality 2-way PA pendant speaker

- 100 V line technique
- 2-way coaxial system
- High-quality sound for speech and music
- White ABS bass-reflex housing with steel grille
- 5 m connection cable with canopy

## Tekniset tiedot:

Active/passive	: passive
Transmission method	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 30/20/15/10/5 W
Impedance	: 8 Ohm
Frequency range	: 80-20,000 Hz (-10 dB) 70-20,000 Hz (-20 dB)

THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 2
Speaker size	: 12 cm
Sensitivity	: 91 dB/W/m
Max. rated SPL	: 106 dB
Radiation angle, horizontal	: 125°
Radiation angle, vertical	: 125°

### Features

Housing material	: ABS
Colour	: white
Mounting device	: ceiling flange
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 185 mm x 230 mm
Width	: 185 mm
Height	: 230 mm
Depth	: -
Weight	: 2.22 kg



Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -