

HSE-70WP - Headworn Microphone

IPX4



Splashproof electret headband microphone, IPX4

- Suitable for vocal and speech applications, especially with outdoor activities or with high ambient humidity
- Very comfortable to wear
- Secure fit also for sports applications
- Back electret microphone cartridge with cardioid polar pattern
- 3-pole mini XLR inline jack for connection to an optional phantom power supply adapter (EMA-1, EMA-300P) or a pocket transmitter TXS-...HSE
- Supplied with nylon bag

Tekniset tiedot:

| | |
|-------------------------|-----------------------|
| Description | : headband microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : cardioid |
| System | : back electret |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : - |
| Operating time | : - |
| Audio frequency range | : 100-14,000 Hz |
| Nominal impedance | : 600 Ohm |
| Sensitivity | : 7.9 mV/Pa |
| S/N ratio | : - |
| Max. sound pressure | : 115 dB |
| Power supply | : DC 1.5-9 V |
| Gooseneck length | : - |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : - |
| Weight | : 60 g |
| Cable | : 1.1 m |
| Connection | : 3-pole mini XLR |