

## HSE-132/SK - Headworn Microphone



Ultra-light headband microphone

- Back electret microphone cartridge
- Cardioid polar pattern
- 3-pole mini XLR inline jack
- Cartridge arm of adjustable length
- Compatible with pocket transmitters TXS-...HSE with 3-pole mini XLR connection
- External power supply, e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Microphone windshield

## Tekniset tiedot:

|                         |                       |
|-------------------------|-----------------------|
| Description             | : headband microphone |
| Version                 | : -                   |
| Transmission method     | : cable               |
| Polar pattern           | : cardioid            |
| System                  | : back electret       |
| Carrier frequency range | : -                   |
| Transmitting power      | : -                   |
| Power supply            | : -                   |
| Operating time          | : -                   |
| Audio frequency range   | : 50-16,000 Hz        |
| Nominal impedance       | : 2 kOhm              |
| Sensitivity             | : 5.6 mV/Pa           |
| S/N ratio               | : -                   |
| Max. sound pressure     | : 130 dB              |
| Power supply            | : DC 1.5-9 V          |
| Gooseneck length        | : -                   |
| Housing material        | : -                   |
| Admiss. ambient temp.   | : 0-40 °C             |
| Dimensions              | : -                   |
| Weight                  | : 17 g                |
| Cable                   | : -                   |
| Connection              | : 3-pole mini XLR     |