
-

Tekniset tiedot:

Peak output power	: 1,400 W
Power rating	: 1,000 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 4 x 250 W
Power rating at 8 Ohm	: 4 x 160 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: 2 x 500 W
bridged operation	
Output impedance	: -
Channels	: 4
Zones	: -
Inputs	: 1.23 V/30 kOhm
Attenuation factor	: -
Frequency range	: 20-20,000 Hz
Crossover network	: 24 dB/oct.
Crossover frequency	: 20-2,500 Hz
Integrated limiter	: yes
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 80 dB
Crosstalk attenuation	: ? 60 dB
THD	: < 0.1%
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 1,800 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 483 mm
Height	: 90 mm
Depth	: 410 mm

Rack spaces, RS	: 2
Weight	: 14.14 kg
Connections	: 4 x XLR, bal.4 x 6.3 mm jack,4 x pair of binding posts