-

Tekniset tiedot:

Peak output power	: 3,000 W
Power rating	: 1,490 W
Power rating at 2 Ohm	: 1 x 1,300Â W (subwoofer)
Power rating at 4 Ohm	: 1 x 850Â W (subwoofer)2 x 320 W (satellite)
Power rating at 8 Ohm	: 1 x 550Â W (subwoofer)2 x 200 W (satellite)
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 3
Zones	: -
Inputs	: 1Â V/19Â kOhm
Attenuation factor	: -
Frequency range	: 20-20,000 Hz
Crossover network	: 12 db/oct.
Crossover frequency	: 70-120Â Hz
Integrated limiter	: yes
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 81 dB
Crosstalk attenuation	: ? 59 dB
THD	: < 0.05%
Mains voltage	: ∼ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 3,200 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 483 mm

Height	: 132 mm
Depth	: 384 mm

Rack spaces, RS	:	3
Weight	:	25 kg
Connections	:	2 x XLR/IN, bal.2 x XLR/par. out,Â bal.4Â x NEUTRIK SPEAKON(sat L/RÂ andÂ 2 x sub par.)