


SPL-2 - Limiter

482 mm
19"

DATEQ
audio technologies



2-channel limiter

- Adjustable via threshold and output
- For sealing
- XLR inputs and outputs

Tekniset tiedot:

| | |
|-----------------------|--|
| Description | : 2-channel limiter |
| Frequency range | : 20-20,000 Hz |
| Control range | : - |
| Control frequencies | : - |
| Input signal | : - |
| Input sensitivity | : - |
| Input impedance | : 10 kOhm |
| Output signal | : - |
| Output impedance | : 600 Ohm |
| Gain | : - |
| Phantom power | : - |
| Compression | : - |
| Gate ratio | : - |
| Crossover frequency | : - |
| High-pass filter | : - |
| Low cut | : - |
| Transmission ratio | : - |
| S/N ratio | : ? 80 dB |
| Channel separation | : - |
| THD | : < 0.05% |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : ∿ 230 V/50 Hz/10 W |
| Dimensions | : 482 x 45 x 175 mm |
| Weight | : 3.2 kg |
| Inputs | : 2 x XLR, bal. |
| Outputs | : 2 x XLR, bal. |
| Other features | : limiter threshold: -14 to +6 dBu,output attenuation: 0 to -40 dB |