PA-4240 - PA Amplifier

482mm 19" | 100V | 4Ω



PA power amplifier

- 4 x 240 W
- Routing switches for parallel operation on 2 channels each
- Temperature-controlled fan
- Connection for external on/off switch
- LED indication for clip, protect, overtemperature and output level
- Mains operation or 24 V emergency power operation

Tekniset tiedot:

Peak output power	:	-
Power rating	:	960 W
Power rating at 2 Ohm	:	-
Power rating at 4 Ohm	:	4 x 240 W
Power rating at 8 Ohm	:	-
Power rating at 16 Ohm	:	-
Power rating at 100 V	:	4 x 240 W
Power rating with 4 Ohm bridged operation	:	-
Power rating with 8 Ohm bridged operation	:	-
Output impedance	:	31Â V/4Â Ohm, 50Â V/10.4Â Ohm, 70Â V/20Â Ohm, 100Â V/42Â Ohm
Channels	:	4
Zones	:	-
Inputs	:	1.2Â V, bal.
Attenuation factor	:	-
Frequency range	:	55-17,000 Hz
Crossover network	:	-
Crossover frequency	:	-
Integrated limiter	:	-
Equalizer bass	:	-
Equalizer midrange	:	-
Equalizer treble	:	-
S/N ratio	:	? 90 dBA
Crosstalk attenuation	:	-
THD	:	< 1%
Mains voltage	:	∼ 230 V
Mains frequency	:	50 Hz
Power consumption, operation	:	2,720 VA
Power consumption, standby	:	-
Standby current	:	-
Operating voltage (possible alternative)	:	DC 24 V
Power supply (possible alternative)	:	DC 113 A
Admiss. ambient temp.	:	0-40 °C
Width	:	483 mm
Height	:	133 mm

Depth	: 370 mm

Rack spaces, RS	:	3
Weight	:	28 kg
Connections	:	4 x XLR (inputs), screw terminals (speakers)