

NBB-75DFIX - BNC Chassis Jack



NEUTRIK UHD BNC panel jacks provide low return loss values at high frequencies, which typically occur in high-definition video signal transmissions. The machined brass body ensures a rugged and non-abrasive connection. Due to being recessed in the D series body (audio industry standard) they are additionally protected.

UHD BNC feed-through panel jack, 75 Ohm, insulated

- Gold-plated cage type contact, optimised for UHD signals like 4 K or 8 K
- High-quality PTFE insulation
- Body with antraloy coating
- BNC insert insulated from the body due to plastic thread
- Earthed panel mounting
- D series
- Colour coding possible
- Compatible with customary BNC cable connectors

Tekniset tiedot:

| | |
|------------------------------|---|
| Description | : panel jack |
| Type | : NEUTRIK BNC feed-through |
| Quantity | : 1 |
| Features | : PTFE insulation, gold-plated contacts |
| Colour/colour coding | : black |
| Power rating | : - |
| Insulating resistance | : $\geq 5 \text{ G}\Omega$ |
| Dielectric strength | : 1.5 kV |
| Certification | : - |
| Pole number | : - |
| Cable inlet | : - |
| Suitable cable cross section | : - |
| Connection | : 2 x BNC, 75 Ω Ohm |
| Strain relief | : - |
| Cable bending protection | : - |
| Stereo | : - |
| Mono | : - |
| Switches | : - |
| Material | : metal |
| Central fixing | : - |
| Contact type | : - |
| No. of contacts | : - |
| Contact width | : - |
| Contact distance | : - |
| Admiss. ambient temp. | : -30+85 °C |
| Dimensions | : - |
| Diameter | : - |
| Length | : - |
| Weight | : 26 g |
| Other features | : D series |