

## PA-5000PTT - Desk Mike



PA desktop microphone (push-to-talk),  
e.g. for connection to PA-5240, PA-5480.

- Push-to-talk button with switching contact for activating the chime at the amplifier
- Connection via screw terminal
- Output for priority function

## Tekniset tiedot:

|                         |   |
|-------------------------|---|
| Description             | : desktop microphone  |
| Version                 | : -   |
| Transmission method     | : cable   |
| Polar pattern           | : -   |
| System                  | : dynamic   |
| Carrier frequency range | : -   |
| Transmitting power      | : -   |
| Power supply            | : -   |
| Operating time          | : -   |
| Audio frequency range   | : 60-18,000 Hz  |
| Nominal impedance       | : 400 Ohm   |
| Sensitivity             | : 1.78 mV/Pa  |
| S/N ratio               | : -   |
| Max. sound pressure     | : -   |
| Power supply            | : -   |
| Gooseneck length        | : -   |
| Housing material        | : -   |
| Admiss. ambient temp.   | : 0-40 °C   |
| Dimensions              | : 126 x 51 x 156 mm (console housing) 270 mm<br>(length of gooseneck) |
| Weight                  | : 725 g   |
| Cable                   | : -   |
| Connection              | : screw terminal  |