

## NAC-3MPHC - PowerCon Chassis Jack



### NEUTRIK POWERCON panel jack

- For mains connection with a high power rating of up to &acd; 250 V/32 A
- Screw connections for ground, phase and neutral connector
- For cable cores: 2.5-6 mm<sup>2</sup>

## Tekniset tiedot:

|                              |   |
|------------------------------|---|
| Description                  | : panel jack  |
| Type                         | : NEUTRIK POWERCON  |
| Quantity                     | : 1   |
| Features                     | : latching device, cable inlet with self-adjusting clamps |
| Colour/colour coding         | : black   |
| Power rating                 | : &acd;Â 250 V/32 A                                       |
| Insulating resistance        | : ? 10Â GOhm  |
| Dielectric strength          | : -   |
| Certification                | : -   |
| Pole number                  | : -   |
| Cable inlet                  | : -   |
| Suitable cable cross section | : -   |
| Connection                   | : NEUTRIK-POWERCON/cable cores 2.5-6Â mm <sup>2</sup>     |
| Strain relief                | : -   |
| Cable bending protection     | : -   |
| Stereo                       | : -   |
| Mono                         | : -   |
| Switches                     | : -   |
| Material                     | : metal   |
| Central fixing               | : -   |
| Contact type                 | : -   |
| No. of contacts              | : -   |
| Contact width                | : -   |
| Contact distance             | : -   |
| Admiss. ambient temp.        | : -25 °C to +70 °C  |
| Dimensions                   | : 32 x 37 x 40.5 mm                                       |
| Diameter                     | : -   |
| Length                       | : -   |
| Weight                       | : 26 g  |
| Other features               | : -   |