
-

Tekniset tiedot:

Impedance (Z)	: -
Transmission method	: 100 V
Frequency range	: 100-18,000 Hz
Resonant frequency (fs)	: -
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 20/15/10/5/2.5 W
Peak music power output (MAX)	: -
Sensitivity	: 89 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: -
Mounting cutout	: $\tilde{\text{A}}$ 104 mm
Mounting depth	: 102 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: $\tilde{\text{A}}$ 132 $\hat{\text{A}}$ mm x 118 $\hat{\text{A}}$ mm
Outside diameter	: $\tilde{\text{A}}$ 132 mm
Width	: $\tilde{\text{A}}$ 132 mm

Height	: -
Depth	: 118 mm
Protective class	: IP44
Admiss. ambient temp.	: 0-40 °C
Weight	: 812 g
Packing unit	: 1
Type of speaker	: 100