
-

Tekniset tiedot:

Camera	: AXC-2812DVM
Design	: dome
Image sensor	: 9 mm (1/2.8") CMOS, 2 megapixels
Number of pixels	: 1920 x 1080 pixels max.
Resolution	: 1080p
Lens	: 2.8-12 mm/1:1.2, motorised zoom
Viewing angle	: 35-85°
Min. illumination	: 0 lx with IR illumination
Webserver	: -
Video streaming	: -
Compression method	: -
Protocols	: -
Protective class	: IP66
Power supply	: DC 12 V/400 mA
Operating voltage	: DC 12 V
Admiss. ambient temp.	: -20 °C to +50 °C
Dimensions	: Å~ 150 mm x 114 mm
Width	: Å~ 150 mm
Height	: 114 mm
Depth	: -
Weight	: 550 g
Other features	: IP66, IR LED, AGC, AWB, DNR
Ethernet	: -
Audio	: -
Video	: TVI, AHD, CVI, CVBS
Video recorder	: AXR-108
Video inputs	: 8 x BNC
Video outputs	: 1 x HDMI, 1 x VGA
Audio inputs	: 8 x RCA
Audio outputs	: 1 x RCA
Resolution	: 1850 x 1080 pixels (25 Å fps)
Video compression	: H.264
Recording	: 200 images/s max.
Menu adjustments	: on-screen menu (OSD)
Recording mode	: manual, alarm, timer, Å motion detector

Search mode	: date and time, event
Lettering	: OSD
Security	: password protection
Video loss detection	: available
Alarm inputs	: 8
Alarm outputs	: 1
Signal device	: integrated
Interfaces	: RS-485, USB 2.0, LAN (RJ45)
Hard disks	: optional, 1 x 8 TB max. (SATA)
Power supply	: DC 12 V/5 A via encl. power supply
Mains voltage	: -
Mains frequency	: -
Power consumption, operation	: -
Power consumption, standby	: -
Operating voltage (possible alternative)	: DC 12 V
Power supply (possible alternative)	: DC 5 A
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 300 x 48 x 225 mm
Width	: 300 mm
Height	: 48 mm
Depth	: 225 mm
Weight	: 1.4 kg