

FGA-22HQ - Cable Adaptor



High-end transformer,
for connecting speaker outputs of a car radio to the line inputs of an amplifier.

- Internal ground separation
- Adjustable output level
- Screw terminals, gold-plated RCA jacks
- Max. input power: 20 W
- Input/output impedance: 45 Ohm/30 Ohm-2.8 kOhm
- Frequency range: 20-30,000 Hz
- THD: < 0.001%
- 42 x 29 x 96 mm, 104 g

Tekniset tiedot:

Description	: transformer
Frequency range	: 20-30,000 Hz
Control range	: -
Control frequencies	: -
Input signal	: -
Input sensitivity	: -
Input impedance	: 45 Ohm
Output signal	: -
Output impedance	: 30Ω Ohm-2.8 kOhm
Gain	: -
Phantom power	: -
Compression	: -
Gate ratio	: -
Crossover frequency	: -
High-pass filter	: -
Low cut	: -
Transmission ratio	: -
S/N ratio	: -
Channel separation	: -
THD	: < 0.001%
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 42 x 29 x 96 mm
Weight	: 104 g
Inputs	: screw terminals
Outputs	: 1 x RCA L/R
Other features	: -