

WSA-24T - Wireless Speaker Adaptor



Wireless stereo transmitter, 2.4 GHz,
for audio streaming.

- Matching the receiver WSA-24R
- Stereo/mono selector switch
- LED for indicating status and peak
- Interference-free operation due to FHSS technology (Frequency Hopping Spread Spectrum)
- Analogue line level input via 6.3 mm jacks L/R and 3-pole XLR L/R
- Metal housing
- Power is provided via enclosed plug-in power supply

djmagazin.de 99

"This set is perfectly suitable for fast and wireless audio transmissions. It features a sophisticated design of neat workmanship. I also like the magnets and the strap which allow for a quick and easy attachment of the receiver. Overall, an excellent set which is available at a favourable price and should definitely be part of any accessory kit."

SOUNDCHECK 02/2016

"All too typical for IMG STAGELINE: the requirements of stage applications are effectively implemented."

tools4music 01/2016

"This compact solution is an excellent aid for every audio supplier ... shows itself ... as a robust and easy-to-use solution for audio streaming."

Tekniset tiedot:

| | |
|--------------------|---|
| Frequency range | : 20-20,000 Hz |
| THD | : < 0.3% |
| Channel separation | : ? 90 dB |
| WLAN | : - |
| Bluetooth | : - |
| Operating range | : ? 30 m with clear view |
| Profiles | : - |
| Codecs | : - |
| Power supply | : via encl. power supply |
| Width | : 130 mm |
| Height | : 54 mm |
| Depth | : 130 mm |
| Weight | : 470 g |
| Connections | : Inputs: 1 x 6.3 mm stereo jack L/R, analogue 1 x 3-pole XLR L/R, analogue |
| Other features | : 2.4 GHz, 25 channels, latency: 18Â ms |