
-

Tekniset tiedot:

Camera	: IOC-2812BV
Design	: bullet
Image sensor	: 8.76 mm (1/2.9") CMOS
Number of pixels	: 2048 x 1536 pixels max.
Resolution	: 3 MP
Lens	: 2.8-12 mm/1:1.2
Viewing angle	: 35-89°
Min. illumination	: 0 lx with IR illumination
Webserver	: -
Video streaming	: mainstream 500-12,000 kbps, substream 100-6,000 kbps
Compression method	: H.265, H.264, MJPEG
Protocols	: HTTP, HTTPS, TCP/IP, RTSP, DHCP, NTP, PoE
Protective class	: IP66
Power supply	: DC 12 V/1 A or PoE
Operating voltage	: DC 12 V
Admiss. ambient temp.	: -20 °C to +50 °C
Dimensions	: Å~ 84 mm x 239 mm
Width	: Å~ 84 mm
Height	: 239 mm
Depth	: -
Weight	: 670 g
Other features	: IP66, IR LED, AGC, AWB, DWDR
Ethernet	: RJ45, 10/100 Mbps
Audio	: -
Video	: -
Video recorder	: IOR-204
Video inputs	: 4 IP-based video channels, 4 x RJ45, LAN with PoE
Video outputs	: HDMIâ„¢, VGA
Audio inputs	: 1
Audio outputs	: 1
Resolution	: 3840 x 2160 pixels max.
Video compression	: H.264, H.265
Recording	: 120 images/s max.
Menu adjustments	: on-screen menu (OSD)

Recording mode

: alarm, motion-triggered, continuous recording, digital
input, manual, timer

Search mode	: -
Lettering	: -
Security	: -
Video loss detection	: -
Alarm inputs	: 4
Alarm outputs	: 1
Signal device	: -
Interfaces	: 1 x RJ45 (10/100 Mbps) 3 x USB 2.0
Hard disks	: optional, up to 1 x SATA II, 8 TB max.
Power supply	: via encl. power supply
Mains voltage	: -
Mains frequency	: -
Power consumption, operation	: -
Power consumption, standby	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 300 x 53 x 227 mm
Width	: 300 mm
Height	: 53 mm
Depth	: 227 mm
Weight	: 750 g